

# SPECIFICATIONS

Model		RTV-X1120 General Purpose	RTV-X1120 Worksite		RTV-X1120 Deluxe	
Body color		Kubota Orange	Kubota Orange	Realtree® AP Camo	Kubota Orange	Realtree® AP Camo
Engine	Make	KUBOTA D1105-E4-UV				
	Type	3-cylinders, 4-cycle, diesel, OHV				
	Displacement	cu.in (cc)	68.5 (1123)			
	Horsepower	HP (kW)/rpm	24.8 (18.5)@3000			
	Cooling system		Liquid			
Transmission		Variable hydro transmission (VHT-X)				
Gear selection		Hi-Lo range forward, neutral, reverse				
Max. traveling speed		mph (km/h)	0-29 (0-46.4)			
4WD system	Front differential	Limited-slip differential				
	Rear differential	Foot operated differential lock				
Steering		Hydrostatic power				
Brakes	Front / Rear	Wet-disc brakes				
	Parking brake	Rear wheel, hand operated				
Suspension	Front suspension	Independent, Dual A-arms with adjustable spring preload				
	Front suspension travel	in. (mm)	8 (205)			
	Rear suspension	Independent with coil over shock				
	Rear suspension travel	in. (mm)	8 (205)			
Ground clearance	Front	in. (mm)	10.5 (266)			
	Rear	in. (mm)	10.4 (263)			
Headlights		Two 37.5 Watt blue-tint halogen, optical axis adjustment				
Occupant Protective System (OPS)	Tubular overhead structure	in. (mm)	2.0 (50.8) steel tube			
	Seat belts	3- point				
	Certification	SAE J2194 and OSHA 1928 ROPS and ANSI B71.9				
Dimensions	Length	in. (mm)	120.3 (3055)	122.5 (3110)		
	Width	in. (mm)	63.2 (1605)			
	Height, overall	in. (mm)	79.5 (2020)			
	Front tread centers	in. (mm)	48.8 (1240)			
	Rear tread centers	in. (mm)	48.8 (1240)			
	Wheelbase	in. (mm)	80.5 (2045)			
Turning radius	ft. (m)	13.1 (4.0)				
Weight	lbs. (kg)	1995 (905)	2061 (935)			
Towing capacity	lbs. (kg)	1300 (590)				
Payload capacity	lbs. (kg)	1510 (685)				
Cargo bed	Material	Steel				
	Width x Length x Depth	in. (mm)	57.7 (1465) x 40.5 (1030) x 11.2 (285)			
	Volume	cu. ft. (m <sup>3</sup> )	15.2 (0.43)			
	Bed height (unloaded)	in. (mm)	34.9 (887)			
	Cargo bed load	lbs. (kg)	1102 (500)			
Dumping system		Manual	Hydro power lift			
Fuel tank capacity	U.S. gals (ℓ)	7.9 (30)				
Sound rating at operator's ear at max rpm		dB. (A)	84			
Tires	Front and rear	ATV	25 x 10-12, 6-ply			
		HDWS	25 x 10-12, 6-ply	—	25 x 10-12, 6-ply	—
		TURF	—			
Front guard design		Simple, center only	Center and bumper		Center, bumper and lens	
Alloy wheel (not available with Turf tire)		Opt.			Std.	
Hydraulic bed lift		Opt.	Std.			
Spray-on bed liner		—	Opt.		Std.	

\*\*"Realtree®" is a registered trademark of Jordan Outdoor Enterprises, Ltd. The company reserves the right to change the above specifications without notice. The values in "Ground clearance" and "Weight" are those of the machine equipped with the tires in the table above. For off-highway use only.

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.